

Model Name	BC-200
Product Name	4K Block Camera
Video Format	2160p 29.97/25 1080p 59.94/50 1080i 59.94/50 720p 59.94/50
Image Sensor	1/2.3" CMOS
Effective Pixels (approx.)	8.93 Mega pixels
S/N Ratio	----
Min. Illumination	50%, High Sensitivity Mode: Color: 0.75 lx (F1.8, AGC on, 1/30 sec) 50%, Normal Mode: Color: 3 lx (F1.8, AGC on, 1/30 sec)
Electronic Shutter	1/25 (1/30), 1/50 (1/60), 1/75(1/90), 1/100, 1/120 (1/125), 1/150(1/180), 1/215(1/250), 1/300(1/350), 1/425(1/500), 1/600(1/725), 1/1000, 1/1250(1/1500)
Zoom Ratio	12x Optical Zoom
Gamma Control	Off / Normal / Standard Mode 1-4
Iris Control	Auto / Manual
Digital Noise Reductions	Yes
Language	English
White Balance	2500K/Sunrise, 3200K/Tungsten, 5600K/Outdoor Manual, One-Push, Auto
AGC / Gain Control	Auto/Manual (0 dB to 33 dB) Max. Gain Limit (9 dB to 33 dB)
Mirror / Flip Image	Yes
Focus Mode	Auto (Sensitivity: normal, low) / One-push AF / Manual / Zoom Trigger AF
Preset	10 Position
Focal Length/ Aperture	f = 3.9 mm (WIDE) to 46.8 mm (TELE) F1.8 to 2.0
Angle of View	Approx. 70.7° (WIDE END) / 6.4° (TELE END)
Image Compensation	Day & Night Function
Video Output	HDMI x2

Tally LED	Dual Color (Red, Green)
RoHS	Compliant
Control Protocol	VISCA / DVIP
Remote Control	RS-422: Transmit up to 1000m DVIP (RJ45): Transmit up to 100m
F/W Update	USB
IR Control	Yes
Camera Control Unit	RMC-180, RMC-300C
Power	DC 12V 15W
Tripod Mount	Hot Shoe Mount
Option	PTR-10 Robotic Pan Tilt Head
Color	Dark Blue
Dimension	71(L) x 183(W) x 83(H) mm
Weight	0.9kg
Operating Temp.	0~40 °C