

| | |
|--------------------------------------|--|
| Model Name | HS-2850 |
| Product Name | HD/SD 12-Channel Portable Video Studio |
| Video Standard | HD & SD |
| Video Format | 3G/HD/SD input: 1080i 50/59.94/60Hz 1080p 25/30/59.94/60Hz HD Output: 1080i 50/59.94/60Hz 1080p 25/29/30Hz SD: 576i 50Hz, 480i 59.94Hz |
| Input Routable / Crosspoint | All 12, repeatable |
| Video Input | Standard: 8x SDI, 2x HDMI Max: 12x SDI, 3x HDMI |
| Computer Graphic Interface | Max 3 via HDMI |
| Down-converted output | 2x SDI |
| Video output | 3x SDI assignable: PGM, PVW, AUX & Clean Out 1x HDMI assignable: PGM & multi-view |
| Audio input | 4x Balanced XLR |
| Audio output | 2x Balanced XLR |
| Embedded audio support | Input up to 16 channels, Output 4 channels |
| Audio Delay Calibration | Up to 8 frames |
| A+V switching | Yes |
| USK | N/A |
| DSK | 2x DSK support Lumakey & Linear key (Key / Fill) |
| Picture in Picture | 2 |
| Logo Insertion | 2 (or 1 logo + 1 clock) |
| Built-in Audio Mixer | N/A |
| Built-in Monitor Display | 17.3" HD TFT LED backlit, 1600x900 pix |
| Built-in Intercom & Tally | 8 channels (4 belt-packs incl.) |
| Dimension (LxWxH) | 455 x 355 x 134 mm |

| | |
|------------------|---|
| Weight | 18.7 Lbs (8.5 Kg), Reinforce Plastic Case |
| Accessory | CB-22H/23H/46/47/60/61/62 |