

| | |
|---|---|
| Model Name | PTC-150W |
| Product Name | HD/SD-SDI PTZ Camera |
| Video format | 1080p 59.94/50/29.97/25 1080i 59.94/50 720p 59.94/50 480i, 576i (on CVBS) |
| Image Sensor | 1/2.8" type progressive scan CMOS sensor |
| Effective Pixels (approx.) | 2.14 Mega pixels |
| S/N Ratio | 50dB |
| Min. Illumination | Color: 0.4 lx B/W: 0.03 lx (F1.6, 1/30 sec, 50IRE, Gain: High) |
| Electronic Shutter | 1/25 (1/30), 1/50 (1/60), 1/75(1/90), 1/100, 1/120 (1/125), 1/150(1/180), 1/215(1/250), 1/300(1/350), 1/425(1/500), 1/600(1/725), 1/1000, 1/1250(1/1500) |
| Zoom Ratio | 30x Optical zoom |
| Gamma Control | Off / Normal / Standard Mode 1-4 |
| Iris Control | Auto / Manual |
| Digital Noise Reductions | Yes |
| On-Screen Display (OSD) | English |
| White Balance | AWB / MWB / One push WB / Outdoor / Indoor / Fluorescent |
| AGC / Gain Control | Auto / Manual Max. Gain Limit |
| Mirror / Flip Image | Yes |
| Focus Mode | Auto / Manual |
| Panning/Tilting Range | Pan: 270°, Tilt: +90° to -20° |
| Panning/Tilting Speed | Manual: 1~150°/Sec Swing: 1~150°/Sec |
| Preset | 50 Position |
| Focal Length | f=4.3 mm (WIDE) to 129 mm (TELE) F1.6 to F4.7 |
| Field of View (Horizontal, Wide) | Approx. 63.7° (WIDE END) / 2.3° (TELE END) |

| | |
|---|--|
| Image Compensation | Day & Night function |
| Video Output | 3G-SDI x1 HDMI x1 CVBS x1 |
| Tally LED | Dual color (Red, Green) |
| Filter | M52.0 x 0.75 Thread with UV Protection |
| RoHS | Compliant |
| Protocol | VISCA, DVIP |
| Remote Control Interface and Transmit Distance | RS-422: Transmit up to 1000m DVIP (RJ45): Transmit up to 100m |
| F/W Update | USB |
| IR Control | Yes |
| Camera Control Unit | RMC-180 |
| Accessories | ---- |
| Color | white |