

Model Name	PTC-200T
Product Name	4K PTZ Camera
Video Format	2160p 29.97/25 1080p 59.94/50 1080i 59.94/50 720p 59.94/50
Image Sensor	1/2.3" CMOS
Effective Pixels	8.93 Mega Pixels
S/N Ratio	----
Min. Illumination	50%, High Sensitivity Mode: Color: 0.75 lx (F1.8, AGC on, 1/30 sec) 50%, Normal Mode: Color: 3 lx (F1.8, AGC on, 1/30 sec)
Electronic Shutter	1/25 (1/30), 1/50 (1/60), 1/75(1/90), 1/100, 1/120 (1/125), 1/150(1/180), 1/215(1/250), 1/300(1/350), 1/425(1/500), 1/600(1/725), 1/1000, 1/1250(1/1500)
Zoom Ratio	12x Optical Zoom
Gamma Control	Off / Normal / Standard Mode 1-4
Iris Control	Auto / Manual
Digital Noise Reductions	Yes
Language	English
White Balance	3200K/ Tungsten, 4200K/ Fluorescent, 5600K/ Outdoor, Manual, One-Push, Auto
AGC / Gain Control	Auto/Manual (0 dB to 33 dB) Max. Gain Limit (9 dB to 33 dB)
Mirror / Flip Image	Yes
Focus Mode	Auto (Sensitivity: Normal, Low), One-Push AF, Manual, Zoom Trigger AF
Panning/Tilting Range	Pan: 270°, Tilt: +90° to -17°
Panning/Tilting Speed	Manual: 1~150°/Sec Swing: 1~150°/Sec
Preset	50 Position
Focal Length/ Aperture	f = 3.9 mm (WIDE) to 46.8 mm (TELE) F1.8 to 2.0

Angle of View	Approx. 70.7° (WIDE END) / 6.4° (TELE END)
Image Compensation	Day & Night Function
Video Output	HDBaseT x 1 3G-SDI x1 HDMI x1
Tally LED	Dual Color (Red, Green)
Control Protocol	VISCA, DVIP
Remote Control	RS-422: Transmit up to 1000m HDBaseT (RJ45): Transmit up to 100m
F/W Update	USB
IR Control	Yes
Camera Control Unit	HS-1500T, HS-1600T RMC-300C
Power	DC 12V 33W
Tripod Mount	1/4-20 UNC
Option	WM-1
Color	Dark Blue
Dimension	173(L) x 189(W) x 219(H) mm
Weight	2.8Kg
Operating Temp.	0~50 °C